


Overview

Product information



DC35-PE-11020000034

Screw type Din-Rail TB, connector method: Screw/plug-in connector,
Number of connectors: 2, Number of potentials: 1, Cross section: 2.5 mm² -
50 mm², AWG: 14 - 1/0, Width: 16 mm, Color: green-yellow, Mounting
type: NS 35/7.5, NS 35/15

Product advantages

- ☒ Steel screw connection technology, reliable connection;
- ☒ Grounding structure, protection circuit;
- ☒ Can be matched with marker strips to avoid incorrect insertion of wires.

Product certification



Technical data

Product drawing

3D model

□

Overview

Number of rows	1
number of connections	2
Open-end side panels	no
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0
Insulating material group	I
standard test	IEC60947-7-2
Connection method	screw connection

Dimension	
width	16mm
End plate width	/
Height	60.8mm
NS 35/7,5 Height	61.3mm
NS 35/15 Height	68.8mm
length	55.4mm
Wiring data	
Strip length	12~13mm
Conductor cross section solid AWG	14~1/0
Conductor cross section solid	2.5~50mm ²
Conductor cross section flexible	2.5~50mm ²
Conductor cross section flexible (ferrule without plastic sleeve)	1.5-35mm ²
Conductor cross section flexible (ferrule with plastic sleeve)	1.5-35mm ²
2 flexible conductors with a TWIN ferrule	1.5-10mm ²
Screw type	Slotted screw
screw thread	M6
Tightening torque	2.5N.m
IEC Electrical parameters	
Rated voltage (III / 3)	/
Rated current (III / 3)	/
IEC Electrical parameters	
Rated surge voltage	8KV
UL Electrical parameters	

Rated voltage	/
Rated current	/

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%
Ambient temperature (storage / transport)	-25°C~60°C

Mechanical performance test

Mechanical strength	Passed the test
Fixing support	Passed the test
Rotational Pull Test	Passed the test

Electrical performance test

Voltage drop	≤3.2mV
Temperature rise test	≤45 K

Safety test

Anti-finger touch	Passed the test
-------------------	-----------------

Environmental protection

RoHS	No excessive harmful substances
REACH SVHC	Lead 7439-92-1

Accessories

Marker

Top marker	/
Side marker	ZT12
Marker support	/

Accessories

Slotted screwdriver size (Blade thickness x Width)	1×6.5
Bridge	/
End cover	/
Partition plate	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Marking & Installation

Marking strip	ZB10
Marker cards	DBE-1

Accessories

End clamp	E-WS
DIN rail	NS35/7.5-1000-00A(H)

Business data

Order number	11020000034
Packing unit	25
Minimum order quantity	25
Products weight (without packaging)	72.008